

	<b>S.C. MultiNET S.R.L.</b> Romania, Baia Mare, Bd. Unirii Nr.11 A/J, Cod: 430271 Tel. 0262-222201, Fax: 0262-220729 <a href="mailto:arpi@multinet.ro">arpi@multinet.ro</a> , <a href="http://www.videocapture.multinet.ro">www.videocapture.multinet.ro</a> R.C.: J24 / 1183 / 1994, C.U.I.: RO 5783680			
<b>26 Ani</b> de Buna Practica in MULTImedia&NETworking	IBAN: RO87 BTRL 0250 1202 A485 12XX Baia Mare			

## MN-PTZ-AT



### Functions & Features


**MN-PTZ-AT** series is a dedicated intelligent auto-tracking camera, with cutting-edge technology in the field of education informatization.

**MN-PTZ-AT** series is built-in with high speed processor, advanced image processing and analysis algorithms to track lecturers and students accurately and quickly, which is in line with the requirements of lecturer capture and remote interactive teaching.

**MN-PTZ-AT** series series adopts advanced ISP technologies and algorithms, to make a vivid image quality, screen brightness uniformity, strong sense of depth, high-definition, and fantastic color rendition.

As a stable, reliable and simple machine to operate, **MN-PTZ-AT** series has full function and high performance. Also it is easy to install and maintain.

Product advantages	Key Features
<ul style="list-style-type: none"> <li>• <b>Integrated design</b> Built-in panoramic camera, to achieve an integrated fusion of panoramic camera and tracking camera.</li> <li>• <b>Advanced tracking algorithms</b> The use of advanced human detection, locking and tracking image processing, analysis algorithm to ensure the target tracking steady, accurate and fast.</li> <li>• <b>Strong anti-interference ability</b> Once the tracking target is locked, it is not affected by the disturbances of other moving objects and projectors etc.</li> <li>• <b>Smooth tracking</b> The sensitivity of action can be adjusted. Tracking target's small movement or gestures will not cause camera's mis-operation.</li> <li>• <b>Video image auto adaptation</b> Based on the distance of tracking target, the tracking camera will automatically zoom and the video image will always maintain the appropriate size and proportion.</li> <li>• <b>Strong environmental adaptability</b> The tracking performance is not affected by classroom's size, shape and seating arrangement.</li> <li>• <b>Ultra wide dynamic exposure function</b> To completely avoid the problem of tracking target darken under the strong light background of projectors etc.</li> </ul>	<ul style="list-style-type: none"> <li>• <b>Superb High-definition Image</b> MN-PTZ-AT employs 1/2.8 inch high quality CMOS sensor. Resolution is up to 1920x1080 with frame rate up to 60 fps.</li> <li>• <b>Leading Focus Technology</b> Leading auto focus algorithm makes lens a fast, accurate and stable auto-focusing.</li> <li>• <b>Low Noise and High SNR</b> Low Noise CMOS effectively ensures high SNR of camera video. Advanced 2D/3D noise reduction technology is used to further reduce the noise, while ensuring image sharpness.</li> <li>• <b>Audio Input Interface</b> Supports 16000,32000,44100,48000 sampling frequency and AAC,MP3,PCM audio coding.</li> <li>• <b>Wide-range, Quiet and Quick Pan/Tilt Mechanism</b> By adopting step driving motor mechanism, MN-PTZ-AT camera works extremely quiet and moves smoothly without any noises.</li> <li>• <b>Multiple Video Compression</b> Supports H.264/H.265 video compression. Supports compression of resolution up to 1920x1080 with frame up to 60 fps and 2 channels 1920x1080p with 30 fps.</li> <li>• <b>Multiple Network Protocol</b> Supports ONVIF, RTSP, RTMP protocols and supports RTMP push mode.</li> <li>• <b>Low-power Sleep Function</b> Supports low-power sleep/wake up, the consumption is lower than 400mW under sleep mode.</li> </ul>

 <b>IBM Advanced Business Partner 2019</b>	 <b>Lexmark Authorised Premium Partner 2019</b>	 <b>HP Silver Partner 2019</b>	 <b>Leading Innovation &gt;&gt;&gt;</b> <b>Gold Partner Service&amp;Sales 2019</b>	 <b>2019</b>	 <b>Dealer Autorizat</b>
--	---	--	--	--	--

	<b>S.C. MultiNET S.R.L.</b> Romania, Baia Mare, Bd. Unirii Nr.11 A/J, Cod: 430271 Tel. 0262-222201, Fax: 0262-220729 <a href="mailto:arpi@multinet.ro">arpi@multinet.ro</a> , <a href="http://www.videocapture.multinet.ro">www.videocapture.multinet.ro</a> R.C.: J24 / 1183 / 1994, C.U.I.: RO 5783680			
<b>26 Ani</b> de Buna Practica in MULTImedia&NETworking	IBAN: RO87 BTRL 0250 1202 A485 12XX Baia Mare			

## Specifications

Parameters/Model	MNET-PTZ-AT-12x	MNET-PTZ-AT-20x
<b>Tracking Camera and Lens Parameter</b>		
Sensor	1/2.8 inch high quality HD CMOS sensor	
Effective Pixels	2.07 megapixel; 16:9	
Video Signals	1080P60/50/30/25/59.94/29.97, 1080i60/50/59.94, 720P60/50/30/25 / 59.94 / 29.97	
Optical Zoom	12x optical zoom f=3.9~46.1mm	20x optical zoom f=4.7~94mm
View Angle	6.3°(tele)~72.5°(wide)	2.9°(tele)~55.4°(wide)
Iris	F1.8 ~ F2.4	F1.6 ~ F3.5
Digital Zoom	X10	
Minimum Illumination	0.5Lux(F1.8, AGC ON)	
Digital Noise Reduction	2D & 3D digital noise reduction	
White Balance	Manual/Auto/One Push/ 3000K/ 4000K/5000K/6500K	
Focus	Auto/Manual	
Aperture	Auto/Manual	
Electronic Shutter	Auto/Manual	
BLC	ON/OFF	
WDR	OFF/Dynamic Range adjustment	
Video Adjustment	Brightness,Color,Saturation,Contrast,Sharpness,Gamma curve	
SNR	>55dB	
<b>Panoramic Camera</b>		
Sensor	1/3 inch high quality HD CMOS sensor	
Effective Pixels	2.1 megapixel	
Lens	Manual Focus	
<b>Input/Output Interface and Protocols</b>		
Video / USB / Serial Interfaces	Model A = HDMI + USB 3.0 + LAN + RS232      Model B = SDI + LAN + RS232	
Network Interface	100M network interface (10/100BASE-TX) 5G WiFi(optional), VISCA	
Network Protocol	RTSP,RTMP,ONVIF,GB/T28181	
Compress Image Code Stream	Dual stream output	
Video Compress Format	H.264,H.265	
Control Signal Interface	RS-232	
Control Protocol	VISCA/Pelco-D/Pelco-P Baud Rate:115200/9600/4800/2400bps	
Audio Input Interface	Dual audio channel 3.5mm linear input	
Audio Compress Format	AAC,MP3,PCM	
Power Interface	HEC3800 power jacket(DC12V)	
<b>Pan Tilt Parameter</b>		
Pan Rotation	-170°~+170°	
Tilt Rotation	-30°~+90°	
Pan Control Speed	0.1 ~100°/s	
Tilt Control Speed	0.1~45°/s	
Preset Speed	Pan: 100°/s,Tilt:45°/s	
Preset Number	User can set up to 255 presets(remoter 10 presets)	
<b>Other Parameters</b>		
Supply Adapter	Input AC110V-AC220V to DC12V/2.5A	
Input Voltage	Output DC12V±10% POE power supply optional	
Input Current	1.5A(Max.)	
Consumption	18W(Max.)	
Store Temperature	-10℃~+60℃	
Store Humidity	20%~95%	
Working Temperature	-10℃~+50℃	
Working Humidity	20%~80%	
Dimension(WxHxW)	254mmX144mmX174mm	
Weight(appr.)	1.54kg	

 <b>IBM Advanced Business Partner 2019</b>	 <b>Lexmark Authorised Premium Partner 2019</b>	 <b>HP Silver Partner 2019</b>	 <b>TOSHIBA</b> Leading Innovation >>> <b>Gold Partner Service&amp;Sales 2019</b>	 <b>Intel Technology Provider 2019</b>	 <b>matrox</b> Digital Video Solutions <b>Dealer Autorizat</b>
--	---	--	--	--	--