

	<b>S.C. MultiNET S.R.L.</b> Romania, Baia Mare, Bd. Unirii Nr.11 A/J, Cod: 430271 Tel. 0262-222201, Fax: 0262-220729 <a href="mailto:arpi@multinet.ro">arpi@multinet.ro</a> , <a href="http://www.videocapture.multinet.ro">www.videocapture.multinet.ro</a> R.C.: J24 / 1183 / 1994, C.U.I.: RO 5783680			
<b>26 Ani</b> de Buna Practica in MULTImedia&NETworking	IBAN: RO87 BTRL 0250 1202 A485 12XX Baia Mare			

## MN-PTZ-CTRL



**MN-PTZ-CTRL** a network (IP Based) PTZ camera controller, is fully compatible with many PTZ camera coding protocols from the main manufacturers in the market, supporting ONVIF, VISCA, Serial port VISCA, PELCO-D/P protocols and etc. This compact camera controller features a high-quality joystick that allows variable speed control, as well as fast camera switching, quick-set camera parameters and so on. The industrial-grade blue screen LCD module has excellent display effect with fine and clear characters.

### Functions & Features

- Supporting ONVIF, VISCA, Serial port VISCA, PELCO-D/P protocols and etc.
- RJ45, RS422, RS232 control interfaces; Control up to 255 Cameras.
- Unique control code learning function allows customers to modify the control code instructions
- Any device on the RS485 bus can be individually configured with different protocols and baud rates.
- All camera parameters can be set through the button operation.
- Metal shell, silicone key design.
- LCD display, keypad sound prompt, real-time display decoder and matrix working status.
- 4D joystick allows variable speed control to cameras
- Maximum communication distance: 1200m(0.5mm Twisted-Pair Cable)

### Specifications

Port	Network: RJ45. Serial Port: RS422, RS232
Protocol	Network : ONVIF, VISCA Serial Port: VISCA, PELCO-D, PELCO-P
Communication BPS	2400bps, 4800bps, 9600bps, 19200bps, 38400, 115200
Interface	5PIN, RS232, RJ45
Joystick	4D ( up, down, left, right, zoom, lock )
Display	LCD Blue Screen
prompt tone	ON/OFF
Power Supply	DC12V±10%
Power Consumption	6W MAX
Working Temperature	-10°C ~ 50°C
Storage Temperature	-20°C ~ 70°C
Environment humidity	≅ 90%RH (nodew)
Dimensions(mm)	320mm ( L ) X179.3mm ( W ) X109.9mm(H)
Upgrade	WEB Upgrading

 <b>IBM Advanced Business Partner 2020</b>	 <b>Lexmark Authorised Premium Partner 2020</b>	 <b>HP Silver Partner 2020</b>	 <b>TOSHIBA</b> Leading Innovation >>> <b>Gold Partner Service&amp;Sales 2020</b>	 <b>2020</b>	 <b>matrox</b> Digital Video Solutions <b>Dealer Autorizat</b>
--	---	--	--	--	--